ANY-LAMP.COM





Specifications Ledvance LED Downlight Alu DN200 25W 2370lm 100D - 840 Cool White | 215mm - IP44



View Product

General Information

| SKU | 233340 |
|--------------------------|-------------------------------------|
| EAN | 4058075091511 |
| Brand | Ledvance |
| Manufacturer Name | DL ALU DN200 25W/4000K WT IP44 LEDV |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 50000 |

Technical Information

| Emergency Lighting | No Emergency Unit |
|-----------------------------|-------------------|
| Tiltable | No |
| Technology | LED Integrated |
| Replaces (Watt) | 2x26 |
| Wattage | 25 |
| Voltage (V) | 220-240 |
| Dimmable | Not Dimmable |
| Colour Code | 840 Cool White |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light colour options | Single Color |

| Driver Included | Yes |
|--------------------------|---------------------------------------|
| Beam Angle (degree) | 100 |
| Luminous Flux (Lumen) | 2370 |
| Luminous Efficacy (lm/W) | 95 |
| Power factor | >0.90 |
| Installation Depth (mm) | 120 |
| Unified Glare Rating | < 28 - for hallways and storage rooms |
| Optical Cover | PMMA (Polymethyl methacrylate) |
| Suitable for Outdoor | No |
| Product Type Category | LED Downlight |

Fixture Information

| Mounting Method | Recessed |
|------------------------|-------------------------------|
| Cut out (mm) | 200 |
| IP-rating | IP44 |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Operating Temperature | -20 to +45 |
| Housing | Aluminium |
| Colour of the Fixture | White |
| Colour of material | White |
| Fixture Connection | PI [Push-in connector 2-pole] |
| Series | DOWNLIGHT ALU |
| | |

Dimensions

| Height (mm) | 61 |
|---------------|-----|
| Diameter (mm) | 215 |

Sensor Information

Why Any-lamp?

Order from the **largest lighting specialist** in Europe (**Customised** quotation







Up to 7 years warranty **Easy** return process

