ANY-LAMP.COM





Specifications Philips LED Downlight Coreline DN145B 6.5W 650lm 90D -830 Warm White | 85mm



View Product

General Information

SKU	237297
EAN	8710163339450
Brand	Philips
Manufacturer Name	DN145B LED6S/830 PSU II WH
Any Lamp all-in warranty	5 Years
Average Lifetime (h)	50000

Technical Information

Emergency Lighting	No Emergency Unit
Tiltable	No
Technology	LED Integrated
Wattage	6.5
Voltage (V)	220-240
Dimmable	Not Dimmable
Colour Code	830 Warm White
Colour temperature (Kelvin)	3000 Warm White
Colour Rendering (Ra)	80-89
Colour of Light	White
Light colour options	Single Color
Including bulb	Yes

Beam Angle (degree) Luminous Flux (Lumen) 650 Luminous Efficacy (lm/W) 100 Power factor >0.90 Installation Depth (mm) 34 Unified Glare Rating <28 - for hallways and storage rooms Optical Cover PC (Polycarbonate) Finish of Reflector PMMA (Polymethyl methacrylate) Product Type Category LED Downlight	Driver Included	Yes
Luminous Efficacy (Im/W)100Power factor>0.90Installation Depth (mm)34Unified Glare Rating< 28 - for hallways and storage rooms	Beam Angle (degree)	90
Power factor >0.90 Installation Depth (mm) 34 Unified Glare Rating <28 - for hallways and storage rooms Optical Cover PC (Polycarbonate) Finish of Reflector PMMA (Polymethyl methacrylate)	Luminous Flux (Lumen)	650
Installation Depth (mm) Unified Glare Rating < 28 - for hallways and storage rooms Optical Cover PC (Polycarbonate) Finish of Reflector PMMA (Polymethyl methacrylate)	Luminous Efficacy (lm/W)	100
Unified Glare Rating < 28 - for hallways and storage rooms Optical Cover PC (Polycarbonate) Finish of Reflector PMMA (Polymethyl methacrylate)	Power factor	>0.90
Optical Cover PC (Polycarbonate) Finish of Reflector PMMA (Polymethyl methacrylate)	Installation Depth (mm)	34
Finish of Reflector PMMA (Polymethyl methacrylate)	Unified Glare Rating	< 28 - for hallways and storage rooms
	Optical Cover	PC (Polycarbonate)
Product Type Category LED Downlight	Finish of Reflector	PMMA (Polymethyl methacrylate)
	Product Type Category	LED Downlight

Fixture Information

EOC8	33945099
Mounting Method	Recessed
Cut out (mm)	65
IP-rating	IP20
Impact Protection (IK)	IK02 - 0.20 joule
Operating Temperature	0 to +35
Housing	Aluminium
Colour of the Fixture	White
Colour of material	White
Fixture Connection	Connection unit 2-pole
Series	DN145B

Dimensions

Height (mm)	28
Diameter (mm)	85

Sensor Information

Type of sensor

No Sensor

Why Any-lamp?

Order from the **largest lighting specialist** in Europe (**Customised** quotation







Up to 7 years warranty **5** Easy return process

