



Specifications Philips LED Panel  
CoreLine RC136B G4 38.5W 5700lm -  
830 Warm White | 60x60cm - UGR<19 -  
Dali Dimmable

[View Product](#)

General Information

|                          |                                       |
|--------------------------|---------------------------------------|
| SKU                      | 253370                                |
| EAN                      | 8720169764125                         |
| Brand                    | Philips                               |
| Manufacturer Name        | RC136B G4 34_43_57S/830 PSD W60L60 OC |
| Any Lamp all-in warranty | 5 Years                               |
| Average Lifetime (h)     | 100000                                |
| Series                   | CoreLine                              |

Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 4x18               |
| Wattage                     | 38.5               |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 830 Warm White     |
| Colour temperature (Kelvin) | 3000 Warm White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |
| Luminous Flux (Lumen)       | 5700               |

|                          |                               |
|--------------------------|-------------------------------|
| Luminous Efficacy (lm/W) | 148.05194805195               |
| IP-rating                | IP20/IP44                     |
| Impact Protection (IK)   | IK03 - 0.35 joule             |
| Fixture Connection       | PI [Push-in connector 3-pole] |
| Power factor             | >0.90                         |
| Product Type Category    | LED Panel                     |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PC (Polycarbonate)             |
| Operating Temperature | -10 to +40                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | Steel                          |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 595     |
| Width (mm)     | 595     |
| Height (mm)    | 38      |

## Sensor Information

## Why Any-lamp?

Type of sensor

No Sensor



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

